

# iD inspiration 55

## Datasheet

| Classification                                       | Norm                                                                                                                                                                                                                                                              | Tarkett Value                                      |
|------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|
| Product type                                         | EN ISO 10582                                                                                                                                                                                                                                                      | Heterogeneous poly(vinyl chloride) floor coverings |
| Domestic classification                              | EN ISO 10874                                                                                                                                                                                                                                                      | 23 Heavy                                           |
| Commercial classification                            | EN ISO 10874                                                                                                                                                                                                                                                      | 33 Heavy                                           |
| Industrial classification                            | EN ISO 10874                                                                                                                                                                                                                                                      | 42 General                                         |
| Technical Characteristics                            | Norm                                                                                                                                                                                                                                                              | Tarkett Value                                      |
| Total thickness                                      | EN ISO 24346                                                                                                                                                                                                                                                      | 2,50 mm                                            |
| Wear layer thickness                                 | EN ISO 24340                                                                                                                                                                                                                                                      | 0,55 mm                                            |
| Total weight                                         | EN ISO 23997                                                                                                                                                                                                                                                      | 3850 g/m²                                          |
| Binder content                                       | EN ISO 10582                                                                                                                                                                                                                                                      | Type I                                             |
| Surface treatment                                    |                                                                                                                                                                                                                                                                   | TEKTANIUM ®                                        |
| Embossing in Register                                |                                                                                                                                                                                                                                                                   | Yes                                                |
| Bevelled edges                                       |                                                                                                                                                                                                                                                                   | No bevel<br>4 sides                                |
| Installation method                                  |                                                                                                                                                                                                                                                                   | Glue-Down                                          |
| Performance for CE Marking                           | Norm                                                                                                                                                                                                                                                              | Tarkett Value                                      |
| Declaration of Performance #                         | EN 14041                                                                                                                                                                                                                                                          | 0132-0084-DoP-2020-03                              |
| Technical Performance                                | Norm                                                                                                                                                                                                                                                              | Tarkett Value                                      |
| Dimensional stability                                | EN ISO 23999                                                                                                                                                                                                                                                      | Average measured value : ≤ 0.10 %                  |
| Curl resultant to heat                               | EN ISO 23999                                                                                                                                                                                                                                                      | ≤  2  mm                                           |
| Reaction to fire                                     | EN 13501-1                                                                                                                                                                                                                                                        | Bfl-s1                                             |
| Residual indentation                                 | EN ISO 24343-1                                                                                                                                                                                                                                                    | ≤ 0,05 mm                                          |
| Furniture leg                                        | EN ISO 16581                                                                                                                                                                                                                                                      | No damage                                          |
| Castor chair                                         | EN ISO 4918                                                                                                                                                                                                                                                       | No damage                                          |
| Impact sound reduction - ΔLw                         | EN ISO 717-2                                                                                                                                                                                                                                                      | 3 dB                                               |
| Reduction of in-room impact noise                    | NF S31-074                                                                                                                                                                                                                                                        | Class C (≤ 85 dB)                                  |
| Thermal resistance                                   | EN ISO 10456                                                                                                                                                                                                                                                      | 0,02 m²•K/W                                        |
| Colour fastness to light                             | EN ISO 105-B02                                                                                                                                                                                                                                                    | ≥ 6                                                |
| Chemical resistance                                  | EN ISO 26987                                                                                                                                                                                                                                                      | Excellent Resistance                               |
| Slip resistance                                      | DIN 51130                                                                                                                                                                                                                                                         | R9<br>R10                                          |
| Slip resistance                                      | EN 13893                                                                                                                                                                                                                                                          | Class DS (μ ≥ 0,30)                                |
| Static Electrical Propensity                         | EN 1815                                                                                                                                                                                                                                                           | Antistatic (≤ 2 kV)                                |
| Underfloor heating                                   |                                                                                                                                                                                                                                                                   | Suitable (maximum 27°C)                            |
| Sustainability performances                          | Norm                                                                                                                                                                                                                                                              | Tarkett Value                                      |
| Total VOC Emissions                                  | EN 16516                                                                                                                                                                                                                                                          | Platinum (≤ 10 µg/m³)                              |
| Material Health Statement                            |                                                                                                                                                                                                                                                                   | Available                                          |
| Recycled content                                     |                                                                                                                                                                                                                                                                   | 39,5 %                                             |
| Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3) |                                                                                                                                                                                                                                                                   | 7,71 kg CO₂e /m²                                   |
| Phthalate - free                                     |                                                                                                                                                                                                                                                                   | Yes                                                |
| Dimensions and designs                               |                                                                                                                                                                                                                                                                   |                                                    |
| Plank                                                | Plank 1200x200mm - 15 planks=3,6 m²/box - 55 boxes/pallet<br>Plank 1200 x 285mm - 11 planks=3,76 m²/box - 54 boxes/pallet<br>Plank 250 x 1500 mm - 10 planks=3,75 m²/box - 56 boxes/pallet                                                                        |                                                    |
| Tile                                                 | Tile 50 x 50 cm / 19,68" x 19,68" - 15 tiles=3,75 m²/box - 52 boxes/pallet<br>Tile 666 x 666 mm - 8 tiles=3,55 m²/box - 40 boxes/pallet<br>Tile 666 x 333mm - 16 tiles=3,55 m²/box - 40 boxes/pallet<br>Tile 500 x 1000 mm - 7 tiles=3,5 m²/box - 54 boxes/pallet |                                                    |
| Number of designs available                          | 100                                                                                                                                                                                                                                                               |                                                    |
| Embossing in register : on Authentics references     |                                                                                                                                                                                                                                                                   |                                                    |
| Slip resistance DIN : R9/R10 depending on embossing  |                                                                                                                                                                                                                                                                   |                                                    |



The above information is subject to modification for the benefit of further improvement (16/03/2022). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.